

# Heavy-Duty Electromagnets

## Air and Oil Cooled



**ACW - Air Cooled Electromagnet**



**OCW - Oil Cooled Electromagnet**

Electro Magnets, trusted technology to recover tramp metals from burden depths up to 1000mm on conveyors up to 2000mm wide. Tailor made coil design to suit any heavy-duty application and performance requirements, ensuring product quality and equipment protection in quarries, mining and recycling facilities.

Bunting's inhouse developed coil design software guarantees needed lifting capacity by combining your application parameters

- Material: burden depth, moisture content, bulk density, flow rate, lump size
- Tramp metal: lump size, shape and weight
- Installation: belt speed, conveyor width, operating environment

The custom made magnetic coil wound in high conductivity NOMEX covered Al-wire is application depended Air and Oil cooled to ensure maximum heat dissipation, enabling a constant high gradient deep reach magnetic field with extraordinary magnetic force.

	<b>ACW - Air Cooled Electromagnet</b>	<b>OCW - Oil Cooled Electromagnet</b>
Magnetic System	Power: 0.6 - 8kW Weight: 0.22 to 8t Size: Up to 1.6m	Power: 1 - 34kW Weight: 0.16 to 34t Size: up to 3m Oil Capacity: 35 - 9654 l

Magnetic System      Extended discharge possible      ATEX rating possible

The magnetic system of the OCW and ACW is incorporated in a robust low carbon steel frame with a manganese steel baseplate to withstand heavy impact of extracted tramp iron.

Both magnetic systems are available to perform as a suspension magnet or as a self-cleaning overband magnet (inline or crossbelt installation).